



## VANISHING OIL 3180

### VANISHING OIL

#### Description

Vanishing Oil 3180 is a low viscosity lubricating fluid. It is excellent for stamping, drawing, forming, slitting, and blanking operations. Vanishing Oil 3180 fills the pores of the metal, bonding to the surface, nearly eliminating friction and wear. This product contains extreme pressure additives. Vanishing Oil 3180 has an easy application and evaporates quickly, leaving only a slight residual protective film. May be used on ferrous and non-ferrous metals.

#### Features & Benefits

- High boiling point
- Low freezing point
- High viscosity index
- Thermal stability
- Corrosion prevention
- High resistance to oxidation
- Water displacing
- No gummy deposits
- Does not attract dirt, dust, and lint

Product Number		Method
Color	<1	D1500
Viscosity @ 40°C, cSt	1.57	D445
Viscosity @ 100°C, cSt	<1.0	D445
Flash, COC °C	142	D92
Pour Point, °C	<-20	D97
Specific Gravity	0.77	D4052
API	51.17	D287
Lbs. Per Gallon	6.45	Calculated

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute essentially a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.*

#### Health & Safety

See the most recent MSDS which is available directly from Precision Fluids, your local salesman, or authorized distributor. Precision Fluids uses only raw materials not listed as carcinogenic by IRAC.

**Precision Fluids • 11850 Tanner Road • Houston, TX 77041**  
**Phone: 713-896-0606 • Fax: 713-896-0610 • [www.precisionfluids.com](http://www.precisionfluids.com)**